



Poly IBC and Tote Adapters

IBC Valve Threads



D1



P1

Name: S60X6 (2") male buttress


Type A

D1: 60mm (2.36")


P1: 6mm (0.24")

Standard: DIN 6131 (Schütz do not use this specification, our adaptors do fit)

Note: Most common thread found on European IBC's



D1



P1

Name: 2" NPS male


Type B

D1: 59.6mm (2.35")


P1: 2.21mm (0.09" - 11.5 TPI)

Standard: ANSI B1.20.1-1983

Note: American National Standard Straight Pipe Thread



D1



P1

Name: 2" Camlock male with 2" BSP

Type C


D1: 63mm (2.48") (59.4mm (2.34") thread)

P1: 2.3mm (0.09" 11 TPI)

Standard: Camlock- A-A-59326 : 1992 Thread – BS 2779 : 1986
Note: Camlock male adapter with added external thread for cheap and compact dust cap



D1



P1

Name: 2" Camlock male with 2 1/8" BSP

Type D

D1: 63mm (2.48") (62.7mm (2.47") thread)


P1: 2.3mm (0.09" 11 TPI)

Standard: Camlock- A-A-59326 : 1992 Thread – N/A

Note: Camlock male adapter with added external oversized thread for cheap and compact dust cap and added seal area for connecting a female Camlock.



D1



N/A

Name: 2" Camlock male adapter

Type E

D1: 63mm (2.48")

P1: N/A

Standard: Camlock- A-A-59326 : 1992

Note: 2" Camlock male adapter fitted to an IBC